

## ST Adaptors

Our ST adaptors have high precision alignment sleeves for reliability and better reconnectability. ST adaptors come with a ceramic sleeve for the singlemode and phosphor bronze sleeve for the multimode. The housing is available in double D footprint type.



### Features

- Complies with IEC 61754-2
- Low insertion loss and high reconnectability capability
- RoHS, REACH SvHC compliant
- Available in simplex or duplex

### Applications

- Data processing networks
- Premises distribution

### Specification

OPTICAL PERFORMANCE	CERAMIC	PHOSPHOR BRONZE	CONFORMANCE
Insertion Loss (Typ)	0.1dB	0.15dB	IEC 61300-3-4
Mating Durability	500	500	IEC 61300-2-2
Receptacle Retention Force	1N - 2.5N	1N - 2.5N	IEC 61754-20
Operating Temperature	-25 to +70, 12 cycles	-25 to +70, 12 cycles	IEC 61300-2-22

### Ordering Information

MODE	TYPE	MODE	PART NUMBER
SM	PC	SIMPLEX	STUZR02
MM	PC	SIMPLEX	STUPHBR
SM	PC	DUPLEX	STUDZR02METAL
MM	PC	DUPLEX	STUDPHBRBEIGE
SM	PC	DUPLEX	STUDZR02BLUE

### Technical Drawing

