

FC Connectors

FC connector features a 2.5 mm ferrule and a threaded coupling nut, for a secure connection in high vibration environments and in lab testing for consistent results.

The FC Connectors are available in Singlemode in both PC and APC and in Multimode PC. The connectors come with standard boots suitable for 900µm, 2mm or 3mm cable diameters.



Features

- Complies with IEC 61754-13 and TIA 604-4-A for intermatability
- Low insertion loss and back reflection capability
- Precision anti rotation key for mechanical stability
- Nickel plated metal body corrosion resistant
- Zirconia ceramic ferrule available in several performance grades
- RoHS, REACH SvHC compliant
- Individual parts packed in bulk package

Applications

- Telecommunication networks
- Local area networks
- Data processing networks
- Distribution application
- Premises distribution
- Test and laboratory equipment

Specification

MECHANICAL PROPERTIES	CRITERIA	EFFECT	CONFORMANCE
Mating Durability	500 matings	<0.2 dB change	IEC 61300-2-2
Vibration	10-55Hz, 0.75 amplitude	<0.2 dB change	IEC 61300-2-1
Drop	Drop height 1m, 5 drops	<0.2 dB change	IEC 61300-2-12
Cable Retention	Magnitude 90N	<0.2 dB change	IEC 61300-2-4
Cable Torsion	1.5kg - 2.5kg for 2mm-3mm cable diameter	<0.2 dB change	IEC 61300-2-5
Operating Temperature	-25°C to +70°C, 12 cycles	<0.2 dB change	IEC 61300-2-22
Cold	-25 for 96 hrs	<0.2 dB change	IEC 61300-2-17
Dry Heat	+70 for 96 hrs	<0.2 dB change	IEC 61300-2-18

FC Connector PC and APC - Singlemode

OPTICAL PERFORMANCE*	GRADE A	GRADE B	GRADE C	GRADE D
IL MAX/Master (Acceptance)	0.10dB	0.15dB	0.25dB	IEC 61300-3-4
IL MAX/Random (97%)	0.20dB	0.30dB	0.40dB	IEC 61300-3-34
Ave/Master	0.08dB	0.12dB	0.18dB	IEC 61300-3-4
Ave/Random	0.08dB	0.12dB	0.18dB	IEC 61300-3-34
Return Loss	55/70dB	55/65dB	55/65dB	IEC 61300-3-6

FC Connector - Multimode

OPTICAL PERFORMANCE*	PREMIUM	STANDARD	CONFORMANCE
IL MAX/Master (Acceptance)	0.15	0.30	IEC 61300-3-4
IL MAX/Random (97%)	0.25	0.40	IEC 61300-3-4
Ave/Master	0.08	0.15	IEC 61300-3-4
Ave/Random	0.10	0.20	IEC 61300-3-4

* Achievable with FibreFab process and specified optical fibre

Ordering Information

Singlemode		GRADE A	GRADE B	GRADE C	
		900µm	FCSM9-H	FCSM9-P	FCSM9
PC	Simplex	2mm	FCSM2-H	FCSM2-P	FCSM2
		3mm	FCSM3-H	FCSM3-P	FCSM3
APC	Simplex	900µm	FCAPC.9MM-H	FCAPC.9MM-P	FCAPC.9MM
		2mm	FCAPC2MM-H	FCAPC2MM-P	FCAPC2MM
		3mm	FCAPC3MM-H	FCAPC3MM-P	FCAPC3MM
Multimode		PREMIUM	STANDARD		
		900µm	FCMM9-P	FCMM9	
PC	Simplex	2mm	FCMM2-P	FCMM2	
		3mm	FCMM3-P	FCMM3	