

## MTRJ Connector

The MTRJ connector is a development of the now legendary MT ferrule. This amazing technology is at the heart of many state-of-the-art connectors. The MT ferrule in its various designs, has the ability to connect anything from 2 fibres in the MTRJ connector, to 12 fibres in the latest versions of the MPO connector.



The Optronics version of the MTRJ, is capable of terminating any 125µm fibre. The flexibility of the connector allows it to be used in short run local area networks in addition to longer haul cabling using singlemode fibre.

It is designed to terminate two fibres within a single connector, reducing the risk of operator error when inter-connecting equipment and distribution panels. The MTRJ has been deliberately designed to look and feel like the industry standard copper connector. The high-density MTRJ connector allows the termination of high fibre count backbone cables into smaller distribution panels.

The MTRJ connector is a high-density small form factor (SFF) connector, designed to reduce the space required in the distribution cabinet. Optronics has a full range of tools and products to assist you with the termination of the MTRJ connector. For those who prefer to purchase pre-terminated pigtails, Optronics can supply all your needs. For information on the full range Optronics MTRJ products and tooling please contact us for a data sheet.

## Specification

DESCRIPTION	SPECIFICATION		
Fibre Type	9/125 µm singlemode	50/125 µm multimode	62.5/125 µm multimode
Fibre Count Available	2	2	2
Insertion Loss (with master plug)	Standard loss: < 0.5 dB	Standard loss: < 0.5 dB	Low loss: < 0.35 dB
Return Loss	!ERROR! expecting operator, implicit multiplication not allowed.		
Cable Type	Mini zip	Mini zip	Mini zip
Adaptor Bulkhead	Single connector / Duplex	Single connector / Duplex	Single connector / Duplex
Intermateability	Optically and mechanically compatible with all equivalent connectors. Compliant with IEC 61754-18		
Product Packaging	Connector in kit form, packaged in 100pcs		
Temperature Cycle	(61300-2-18)	-40 to +75°C, 40 cycles	< 0.2dB change
High Temperature	(61300-2-18)	70°C for 96 hours	< 0.2dB change
Operating Temperature	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Vibration (mated pair)	(61300-2-1)	10-55 Hz, 1.5mm P to P	< 0.2dB change
Mating Durability	(61300-2-2)	500 mating cycles Clean every 25	< 0.2dB change
Damp Heat	(61300-2-19)	40°C at 93% RH, 96 hours	< 0.2dB change

## Ordering Information

Description	Part No.
MTRJ Connector	MTRJUNITER